

Product data sheet

E-ISM guide rail TS

5000



With closing sequence control, electrical hold-open device
on both leaves and levers

E-ISM guide rail TS 5000



AREAS OF APPLICATION

- Double leaf doors with closing sequence control
- Hold-open systems with integrated hold-open device
- Installation on hinge side
- Right and left single-action doors
- Symmetrical and asymmetrical division of door possible
- Up to 2800 mm hinge clearance
- Minimum hinge clearance 1300 mm, minimum width of passive leaf 400 mm

PRODUCT FEATURES

- Electric hold-open device in the guide rail with hold-open area of 80°–130°
- Retention force of the electromechanical hold-open device can be variably adjusted
- Operating voltage 24 V DC
- Closing sequence control holds the active leaf in the waiting position until the passive leaf is closed
- Vandalism protection through flexible Bowden cable
- Horizontally adjustable in the installation position by 4 mm through elongated holes
- With screwed slide block

TECHNICAL DATA

Productname	E-ISM guide rail TS 5000
Input voltage	24 V DC
Electrical power consumption	4.8 W
Duty rating	100 %
Residual ripple	20 %
IP rating	IP43
Minimum hinge clearance	1300 mm
Minimum passive leaf width	400 mm
Standard conformity	EN 1155. EN 1158
Length	2630 mm
Width	40 mm
Height	30 mm
opening restrictor upgradable	Yes
Hold-open function	Electrical
Hold-open device on the active leaf / passive leaf	Yes / Yes
Hold-open device can be overridden	Yes

E-ISM guide rail TS 5000



Hold-open range	80 ° - 130 °
Smoke switch integrated	No
Closing sequence control integrated	Yes
Height correction possible	Yes
Flexible opening restrictor	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	EAN	Colour	Dimensions
E-ISM guide rail TS 5000	continuous, with integrated closing sequence control, electrical hold-open device and levers on both sides	115603	4042938156035	Stainless steel optic	2630 x 40 x 30 mm
E-ISM guide rail TS 5000	continuous, with integrated closing sequence control, electrical hold-open device and levers on both sides	115600	4042938156004	silver-coloured	2630 x 40 x 30 mm
E-ISM guide rail TS 5000	continuous, with integrated closing sequence control, electrical hold-open device and levers on both sides	115602	4042938156028	white RAL 9016	2630 x 40 x 30 mm
E-ISM guide rail TS 5000	continuous, with integrated closing sequence control, electrical hold-open device and levers on both sides	115604	4042938156042	according to RAL	2630 x 40 x 30 mm

ACCESSORIES

FLEXIBLE OPENING RESTRICTOR

For E and R guide rails, 1- and 2-leaf



Designation	Description	Ident-No.	EAN	Material
Flexible opening restrictor	for guide rail 1-leaf: TS 5000 E/R/RFS (door leaf installation), Boxer E; 2-leaf: all E/R/ISM variants TS 5000 (incl. VPK) and Boxer	145311	4042938453110	Plastic

E-ISM guide rail TS 5000



INSTALLATION MATERIAL

MOUNTING PLATE GUIDE RAIL

For ISM and E-ISM guide rail



Designation	Description	Ident-No.	EAN	Colour	Type
Mounting plate guide rail	for ISM / E-ISM guide rail	118702	4042938187022	silver-coloured	
Mounting plate guide rail	for ISM / E-ISM guide rail	118703	4042938187039	according to RAL	